



NetStream 5x750 D

NetStream 5x750 D is a carrier-class radio that supports 5.1 to 6.0 GHz and complies with FCC, IC (Canada), MII (China), WPC (India) and Universal regulations (factory default: 5.8 GHz FCC/IC).

NetStream 5x750 D provides 750 Mbps net aggregate throughput at a range of up to 40 km/25 miles.

NetStream 5x750 D is connectorized for external antenna (2 x N-type).

Product Highlights

- 750 Mbps Ethernet net throughput
- Long range – up to 120 km/75 miles
- Telco-grade, extremely robust in harsh conditions
- Supports intra-site and inter-site TDD synchronization to maximize network capacity
- Adaptive asymmetric throughput – dynamic allocation between uplink and downlink
- Advanced OFDM and MIMO technologies for operation in nLOS/NLOS and dense radio environments
- Robust and reliable to operate in tough conditions and extreme temperatures



Product Specifications

Configuration

Architecture	Outdoor Unit Connectorized for external antenna (2 xN-type)
IDU to ODU Interface	Outdoor CAT-5e cable; Maximum cable length: 100 m for 10/100BaseT and 75 m for 1000BaseT

Radio

Capacity	750 Mbps net aggregate throughput
Range	Up to 120 km / 75 miles
Channel Bandwidth	Configurable: 10, 20, 40 or 80 MHz (for the default band)
Modulation	2x2 MIMO-OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)
Adaptive Modulation & Coding	Supported
Automatic Channel Selection	Supported upon power up
DFS	Not Supported (for the default band)
Diversity	Supported
Spectrum Viewer	Supported
Max Tx Power	25 dBm
Duplex Technology	TDD
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6
Encryption	AES 128; FIPS 197
Supported Indoor Units	NetStream PoE device
Bandwidth Allocation	Configurable: Symmetric or Asymmetric
QoS	Packet classification to 4 priority queues according to 802.1p and Diffserv
VLAN Support	802.1Q, QinQ, 4094 VLANs
TDD Intra Site Synchronization	Supported
TDD Inter Site Synchronization	Supported through common GPS receiver per site

Supported Bands

Band	Channel BW 10 MHz	Channel BW 20 MHz	Channel BW 40 MHz	Channel BW 80 MHz	Radio Compliance
5.8 GHz FCC/IC*	5.725 - 5.850	5.725 - 5.850	5.725 - 5.850	5.725 - 5.850	FCC 47CFR Part 15.247; IC RSS-210
5.1 GHz Universal	5.145 - 5.340	5.140 - 5.345	5.130 - 5.355	5.130 - 5.375	Universal
5.1 GHz FCC/IC	5.160 - 5.245	5.160 - 5.245	5.155 - 5.250	5.155 - 5.250	FCC 47CFR Part 15.407; IC RSS-210
5.4 GHz Universal	5.470 - 5.725	5.465 - 5.730	5.455 - 5.740	5.455 - 5.760	Universal
5.8 GHz MII China	5.735 - 5.840	5.730 - 5.845	5.720 - 5.855	5.700 - 5.875	CMIIT RTA
5.8 GHz WPC	5.825 - 5.875	5.825 - 5.875	5.815 - 5.885	-	WPC (India) G.S.R 38(E) dated 19 January, 2007 Notification
5.9 GHz Universal	5.725 - 5.955	5.720 - 5.960	5.710 - 5.970	5.710 - 5.990	Universal
6.0 GHz Universal	5.695 - 6.055	5.690 - 6.060	5.680 - 6.070	5.680 - 6.090	Universal

* Default Band

Mechanical

ODU Dimensions	28(w) x 19.5(h) x 8(d) cm
ODU Weight	2.4 kg / 5.29 lbs

Power

Power Feeding	Power provided over ODU-IDU cable
Power Consumption	<20 W

Environmental

Operating Temperatures	-35°C to 60°C / -31°F to 140°F
Humidity	100% condensing, IP67 (totally protected against dust and against immersion up to 1 m)

Safety

FCC/IC (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22
ETSI	EN/IEC 60950-1, EN/IEC 60950-22

EMC

FCC	CFR47 Class B, Part15, Subpart B
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4
CAN/CSA-CEI/IEC	CISPR 22-04 Class B

