

IDU FE DC



IDU FE DC is a DC Power over Ethernet (PoE) device provides data and power to NetStream outdoor units.

Product Specifications

Electrical	
DC Input Voltage	-20 to -60 VDC (single input)
Output Voltage Out voltage	48 VDC
Power Consumption	0.6 W (not including radio)
Output Voltage and Current	Typical: 55 VDC, 0-1A Range: 50-58 VDC
Protection	Differential – 15 KW Common – 3 KW
LAN interface type	10/100BaseT Interface (Line Impedance -100 ohm)
Power On indication	Green: Power On
Environmental	
Operating Temperatures	-5°C - 45°C/23°F - 113°F
Humidity	Up to 90% non-condensing
Safety	
FCC/IEC/CAN/CSA	60950-1
EMC	
ETSI	EN 300 386 V1.3.2; EN 301 489-1 V1.4.1
FCC	CFR47 Class B, Part15, Subpart B
CAN/CSA	ICES-003:2004 class B
AS/NZS	CISPR 22:2006 Class B
Mechanical	
Case	Plastic
Dimensions	22 cm (W) x 17 cm (D) x 4.4 cm (H)
Weight	0.5kg / 1.1lbs
Interfaces	
DC Input	2 pins connector
ODU	RJ-45
Ethernet	RJ-45